



注：L 随整机长度而定，但最长不得超过4米。

⑪	GB93-87	弹垫 10	2																
⑩	GB97.2-85	平垫 10	2																
⑨	GB5782-86	螺栓M10x45	2																
⑧	GB93-87	弹垫 16	3																
⑦	GB97.2-85	平垫 16	3																
⑥	GB5782-86	螺栓M16x35	2																
⑤	GB93-87	弹垫 10	6																
④	GB97.2-85	平垫 10	6																
③	GB5780-86	螺栓M10x30	6																
②	YF07.3	直角管接头M10x1	1																
①	YF05.3	铜管接头M10x1	1																

13	LSY230-217	观察孔盖	1	Q235															
12	LSY230-218	连接管 $\phi 194 \times 6$	1	20															
11	LSY230-211	吊耳	2	Q235															
10	LSY230-210	大叶片		16Mn															
9	LSY230-302	芯管	1	20															
8	LSY230-208	花键轴堵	2	Q235															
7	LSY230-207	内花键套	2	40Cr															
6	LSY230-206	中心花键轴	1	40Cr															
5	LSY230-205	吊座滑动轴承	1	锌基合金															
4	LSY230-204	轴承吊座	1	ZG270~500															
3	LSY230-203	过油螺栓	1	45															
2	LSY230-301	无缝钢管	1	20															
1	LSY230-201	管体连接法兰	2	Q235															

序号	代号	名称	数量	材料	单件重量	总计重量	备注		
第二部分传动部装							LSY230-300		
标记	处数	更改文件号	签名	日期	阶段标记	重量	比例	共张	第张
设计	李连通		工艺						
校对	秦海波		标准						
审核	刘飞		批准						